

## Specification Sheet

## NANOMYTE® BE-10E (LTO)

### POWDER CHARACTERISTICS

---

<b>Chemical Name:</b>	Lithium Titanium Oxide
<b>Formula:</b>	$\text{Li}_4\text{Ti}_5\text{O}_{12}$
<b>Purity:</b>	> 98%
<b>Average Particle Size (APS):</b>	1.5 – 3 $\mu\text{m}$
<b>Specific Surface Area:</b>	5 – 9 $\text{m}^2/\text{g}$

### ELECTRODE TAPE CHARACTERISTICS

---

<b>Standard Substrate:</b>	Aluminum
<b>Standard Sheet Size:</b>	5 in x 10 in (12.7 cm x 25.4 cm)
<b>Active Material Loading:</b>	80%
<b>Typical Active Material Loading:</b>	6 – 7 $\text{mg}/\text{cm}^2$
<b>Tape Thickness:</b>	25 – 50 $\mu\text{m}$

### ELECTRICAL CHARACTERISTICS

---

<b>Average voltage vs. Li/Li<sup>+</sup>:</b>	1.5V
<b>Minimum capacity:</b>	150 mAh/g
<b>Nominal capacity at 0.1C:</b>	≥ 170 mAh/g

### RECOMMENDED OPERATING CONDITIONS

---

<b>Maximum Charge Current:</b>	5C
<b>Maximum Discharge Current:</b>	10C

### STORAGE & HANDLING

#### Conditions for Safe Storage

Store in a dry and well-ventilated place. Avoid moisture.

#### Precautions for Safe Handling

Appropriate personal protective equipment should be used at all times. Avoid contact with eyes and skin. Wash hands thoroughly after handling.

**Refer to MSDS for further information.**